



NOTES:

1. MAINTAIN PAVER BAND WIDTH OF 450mm EXCEPT WHERE REQUIRED TO ADJUST PAVERS TO SUIT SITE CONDITIONS, THEN MIN 400mm BAND WIDTH OVER MIN 5 COURSES IS ACCEPTABLE.
2. 1-3mm GAP REQUIRED BETWEEN PAVERS.
3. FOOTWAY STONE SETTS TO COMPLY WITH THE FOLLOWING
 - 3.1. NATURAL STONE MATERIAL
 - 3.2. TO BE SIZED TO FIT WITHIN 450mm WIDE PAVER BAND
 - 3.3. LAYED ON 200mm THICK 32Mpa REINFORCED (2 LAYERS OF SL82) CONCRETE BASE
 - 3.4. DESIGNED FOR HEAVY VEHICLE LOADS
 - 3.5. MEET SLIP RESISTANCE OF MINIMUM 'W' AS PER HB197
4. ALL DIMENSIONS IN MILLIMETRES UNLESS OTHERWISE STATED

STONE SIZES:

TYPE A: 900 x 450 x 60mm
 TYPE B: 600 x 450 x 60mm
 TYPE C: 450 x 450 x 60mm
 TYPE D: 300 x 450 x 60mm

CJ: CONTRACTION JOINT
 EJ: EXPANSION JOINT

PLAN 1:50