



GRANITE PAVING
REFER TO 2.2.1

EJ & CJ
REFER TO 2.2.5

REFER TO 2.2.16

DISH/VALLEY

CLOSURE UNITS VARY IN LENGTH
AS DETERMINED BY PATTERN.
MINIMUM UNIT LENGTH OF 300mm.
NON-STANDARD CUT PAVERS

300mm HIGH X 300mm
WIDE STONE KERB AT
TRAM STATION

STONE SETTS
REFER TO 2.2.13

NOTE:

1. MAINTAIN PAVER BAND WIDTH OF 450mm EXCEPT WHERE REQUIRED TO ADJUST PAVERS TO SUIT SITE CONDITIONS, THEN MIN 400mm BAND WIDTH OVER MIN 5 COURSES IS ACCEPTABLE.
2. 1-3mm GAP REQUIRED BETWEEN PAVERS.

STONE SIZES:

- TYPE A: 900 x 450 x 60mm
- TYPE B: 600 x 450 x 60mm
- TYPE C: 450 x 450 x 60mm
- TYPE D: 300 x 450 x 60mm

CJ: CONTRACTION JOINT
EJ: EXPANSION JOINT

PLAN 1:50

NOTE: ALL DIMENSIONS IN MILLIMETRES UNLESS OTHERWISE STATED