



NOTES:

1. MAINTAIN PAVER BAND WIDTH OF 450mm EXCEPT WHERE REQUIRED TO ADJUST PAVERS TO SUIT SITE CONDITIONS, THEN MIN 400mm BAND WIDTH OVER MIN 5 COURSES IS ACCEPTABLE.
2. 1-3mm GAP REQUIRED BETWEEN PAVERS.
3. TACTILES AS REQUIRED
4. ROAD PAVING TO COMPLY WITH THE FOLLOWING REQUIREMENTS
 - 4.1. LAYED ON A 200mm THICK 32mpa REINFORCED (2 LAYERS OF SL82) CONCRETE BASE
 - 4.2. A NATURAL STONE PAVER WITH SIMILAR COLOUR TO AUSTRAL BLACK GRANITE PAVING
 - 4.3. DESIGNED FOR HEAVY TRAFFIC LOADS EQUIVALENT TO CLASS D
 - 4.4. TO MEET THE RMS SKID RESISTANCE REQUIREMENTS
 - 4.5. DEMONSTRATED TO HAVE MINIMAL POLISHING OVER TIME DUE TO TRAFFIC LOADS
 - 4.6. PAVING TO BE DESIGNED FOR QUICK MAINTENANCE ALLOWING FOR TRAFFIC LOADING AFTER REPAIR
 - 4.7. MINIMUM SERVICE LIFE OF PAVEMENT SHALL BE 40 YEARS

STONE SIZES:

- TYPE A: 900 x 450 x 60mm
 TYPE B: 600 x 450 x 60mm
 TYPE C: 450 x 450 x 60mm
 TYPE D: 300 x 450 x 60mm

- CJ: CONTRACTION JOINT
 EJ: EXPANSION JOINT

PLAN 1:100

NOTE: ALL DIMENSIONS IN MILLIMETRES UNLESS OTHERWISE STATED