



**NOTES:**

1. ALL STEEL COIL TO CONFORM TO AS/NZS 1594 GRADE HU300 U.O.N.
  2. ALL STEEL PLATES TO CONFORM TO AS/NZS 3678 GRADE 250 U.O.N.
  3. ALL STEEL BARS AND SECTIONS TO CONFORM TO AS/NZS 3679 GRADE 250 U.O.N.
  4. ALL WELDS TO CONFORM TO AS/NZS 1554 PART 1
  5. ALL TAPER LOCK JOINT LENGTHS ARE NOMINAL U.O.N.
- IN ACCORDANCE WITH AS/NZS 4680

Supplied with 1" BSP screw-on cap.

External thread 1" BSP x 40 lg.

5 sets of M6 x 40 lg. S/Steel studs each fitted with 3 brass nuts and 1 brass washer.

DETAIL B. NTS.

SECTION A-A. NTS.

DETAIL A. NTS.

DOOR DETAIL

PAINT WITH DULUX DUREBILD STE.

Available for cable access.

4 slots  $\phi 28$  equi-spaced on 330 PCD. To suit M24 foundation bolts. Base plate 330 x 330.

SCALE: NTS

NOTE: ALL DIMENSIONS IN MILLIMETRES UNLESS OTHERWISE STATED